

# Geoprobe 6011DT Drill Rig



### Base Unit Weight: 4,800 lb. (2,177 kg)

**WEIGHT & DIMENSIONS** 





# TOOLING

## Typical Geoprobe® Tooling for the 6011DT

- 60 in. Direct Push Tooling
- Probe Rod Sizes: 3.75 in., 3.25 in., 2.25 in., 1.5 in., 1.25 in.\*
- Macro Core® Soil Sampling (MC5, MC7)
- Dual Tube Soil Sampling (DT37, DT325, DT22)
- Groundwater Sampling (SP22, SP16)
- · Prepacked Monitoring Well Installations (2.0 in., 1.5 in., 1.0 in., 0.75 in.)
- Direct Image® Tooling

#### \* Center Rod Use Only

Rig shown with optional features. Weights & dimensions subject to change without notice



# **OPTIONS**

#### **Rotary Head**

• 2-Speed Rotary Head (2,500 ft-lbs)

#### **Drill Mast**

- Low Clearance Mast CylinderCPT Valve Kit

#### **Rotational Safety Cage**

• Rotation Guard

#### **Pumps**

• Moyno® 2L4 Pump Kit

### **Hydraulic Extruder**

• 5 ft. Hydraulic Extruder Kit

#### **Toolboxes & Rodracks**

- Rod Rack
   Control Panel Side Storage
   Drop Rack System with Rod Rack
   Drop Rack System with Utility Rack
   Yoke Vise & Mounting Bracket Kit, Horizontal
   25 gal. Water Transport System
   Rear Blade Forks (1200 lbs. max.)

#### **Additional Options**

- Head Feed Down Control Kit
  CE Compatible Remote Control Kit
  CE Inclinemeter Kit



Great for indoor spaces with available low-clearance cylinder option



Videos, Photos, Specifications, Resources geoprobe.com/6011dt